## Cleaning and maintenance - pigmented oil

Daily cleaning is done with a soft cloth wrung out in warm water. Avoid using cleaning agents or chemicals. Pigmented oil provides the furniture with a durable surface, so retreatment is not necessary.

For repair of scratches and minor wear, a maintenance kit with pigmented oil should be used, which can be obtained from CHS customer service.

The maintenance kit consists of a pigmented base oil, clear top oil, sanding sponge, wiping cloth, and sponge for applying oil.

Repair of scratches and minor wear with pigmented oil

- 1. First, clean the surface. Stains and dirt should be completely removed before oil treatment to achieve the best result.
- 2. Lightly sand the affected area with the sanding sponge. Always sand in the direction of the grain.
- 3. Shake the bottle of pigmented oil thoroughly.
- 4. Apply the pigmented oil evenly and thinly on the worn area with the sponge. Then wipe off excess oil with the wiping cloth. Make sure to wipe the oil thoroughly along the edges to blur the transition from the repaired area to the rest of the table.
- 5. Allow the pigmented oil to dry completely for at least two days. If the desired result is not achieved, repeat step 4. It may be necessary to repeat the treatment several times to achieve the right color tone.
- 6. When the pigmented oil is completely dry, apply the protective clear top oil with the sponge. Let the top oil sit for about 10 minutes, then wipe off the excess oil.
- 7. Before using the table again, the oil must be completely dry. The drying time of the oil varies depending on the temperature, so always check for smudging before using the table.

Note that color differences may occur to a greater or lesser extent during repairs.

WARNING! Be aware that cloths or sponges used for oil treatment can self-ignite, so they should always be stored in an airtight metal or glass container. This also applies if the cloths are disposed of.

